





welldana®



	Welldana Varenummer	34-180628	34-180630	34-180632	34-180640	34-180642
<b>Info</b>	Til pool (m <sup>3</sup> )	30-60	40-75	50-95	65-120	90-160
	Type	Full Inverter				
	Kølemiddel	R32				
	Volt / Hz	230V~ / 50Hz	230V~ / 50Hz	400V/3N~ / 50Hz	400V/3N~ / 50Hz	400V/3N~ / 50Hz
	Funktion	Opvarmning og køling				
	Godkendelse	CE				
	<b>Parameter</b>	<b>Ydelse ved luft 15<sup>0</sup> og vand 26<sup>0</sup>. Luftfugtighed 70%</b>				
Kapacitet opvarmning (KW)		2.3~9.5	2.87~12.5	4.65~16.0	4.57~19.2	5.57~22.7
Forbrug (kW)		0.32~2.03	0.41~2.55	0.63~2.92	0.80~3.98	0.80~5.04
COP		7~4	7~4	7.38~5.48	6.96~4.82	6.96~4.50
Nominal strøm (A)		15.0	15.0	10.0	15.0	15.0
Max strøm (A)		20.0	20.0	20.0	20.0	20.0
Laveste driftstemperatur		-15 C	-15 C	-15 C	-15 C	-15 C
Blæser hastighed (RPM)		400-600	400-600	400-600	400-600	400-700
Lydeniveau (Sound Pressure) 1m dB(A)		40-48	41-48	44-50	45-52	45-54
Tilslutning (mm)		50				
Anbefalet driftsflow (m3/h)		6.5	7	8.9	9.1	9.7
Max tryktab (max) MMS		5.5	6	6	11	11
<b>Visuelt</b>	Kabinet	Pulverlakeret metalkabinet				
		Black				
	<b>Display</b>					
	Display	Bluetooth display og vandtæt boks				
	Montage					
<b>Tilbehør</b>	<b>Smart Control</b>					
	Wifi Modul & APP	Ja				
	Manual	DK/UK/SE	DK/UK/SE	DK/UK/SE	DK/UK/SE	DK/UK/SE
	Vibrationsdæmpende ben	Ja/gummi	Ja/gummi	Ja/gummi	Ja/gummi	Ja/gummi
Tilslutning (mm)	Ø 50 mm	Ø 50 mm	Ø 50 mm	Ø 50 mm	Ø 50 mm	
Rubber Ring	Rubber	Rubber	Rubber	Rubber	Rubber	
Dræn tilslutning	Gummi	Gummi	Gummi	Gummi	Gummi	